
Set Operations and Subqueries – Key Points

- JOIN creates a new table with more columns
 - new rows are pairwise combinations of rows from the original relations
- UNION creates a new table with more rows
 - new rows are the rows from either of the original relations
 - removes duplicate rows; use UNION ALL to keep duplicates
- JOIN, NATURAL JOIN lose rows with no match in the other table
- OUTER JOIN keeps those rows, filling in with NULL values
- subqueries in FROM allow building up a more complex table from which to draw the result
- subqueries in WHERE allow more complex conditions for choosing rows
 - including conditions where one row is compared against another



OUTER JOIN

Join combines matching rows in two relations. But what if a row in one relation has no match in the other?

An OUTER JOIN includes rows with no match in the other relation, filling in the missing columns with NULL.

- R LEFT OUTER JOIN S includes rows in R with no match in S
- R RIGHT OUTER JOIN S includes rows in S with no match in R
- R FULL OUTER JOIN S includes both rows in R with no match in S and rows in S with no match in R

OUTER JOINs can be NATURAL or include an ON condition.

Note: MySQL does not support full outer joins.

CPSC 343: Database Theory and Practice • Fall 2024

16

UNION

```
( SELECT ... )
UNION
( SELECT ... )
```

result consists of the rows from both result sets.

Notes.

- columns need to match in number, order
- columns should match in data type
- does not include duplicates
 - · use UNION ALL instead to keep

CPSC 343: Database Theory and Practice • Fall 2024

17

```
( SELECT Lname, Sex
  FROM EMPLOYEE )
UNION
( SELECT E.Lname, D.Sex
  FROM EMPLOYEE E JOIN DEPENDENT D ON E.Ssn=D.Essn )
```

SQL Operations on Relations

operation	meaning	notes
EXISTS R	true if and only if R is not empty	
s IN R	true if and only if s is a row of R	
s > ALL R	true if and only if s is greater than every value in \ensuremath{R}	also >=, <. <=, =, <>
s > ANY R	true if and only if s is greater than at least one value in \ensuremath{R}	also >=, <. <=, =, <>

can also prefix with NOT

CPSC 343: Database Theory and Practice • Fall 2024

CPSC 343: Database Theory and Practice • Fall 2024

• NOT EXISTS R, s NOT IN R, NOT s > ALL R, etc

All of these operations work when R has only one column. Many of them also make sense when R has multiple columns, if s has the same columns as R.

Subqueries in WHERE

If the subquery returns only a single value (one column, one row), it can be used like a constant.

```
SELECT *
FROM EMPLOYEE
WHERE Ssn = ( SELECT Mgr_ssn
FROM DEPARTMENT
                 WHERE Dnumber=5 )
```

SQL Operations on Relations

operation	meaning	notes
EXISTS R	true if and only if R is not empty	
s IN R	true if and only if s is a row of R	
s > ALL R	true if and only if s is greater than every value in \ensuremath{R}	also >=, <. <=, =, <>
s > ANY R	true if and only if s is greater than at least one value in R	also >=, <. <=, =, <>

- can also prefix with NOT
- NOT EXISTS R, s NOT IN R, NOT s > ALL R, etc

All of these operations work when R has only one column. Many of them also make sense when R has multiple columns, if s has the same columns as R.

CPSC 343: Database Theory and Practice • Fall 2024

Correlated Subqueries

This is a *correlated subquery* – it must be evaluated for every row of the FROM relation because its result depends on the current row.

Compare to

SELECT *
FROM EMPLOYEE
WHERE Ssn = (SELECT Mgr_ssn
FROM DEPARTMENT
WHERE Dnumber=5)

The subquery will return the same value every time, so it could be evaluated once and then treated as a constant.

CPSC 343: Database Theory and Practice • Fall 2024

22

CPSC 343: Database Theory and Practice • Fall 2024

24

```
SELECT Fname, Lname, Ssn
FROM EMPLOYEE E
WHERE Sex IN ( SELECT Sex FROM DEPENDENT D WHERE E.Ssn=D.Essn )
```

```
SELECT *
FROM EMPLOYEE E
WHERE NOT EXISTS ( SELECT *
FROM EMPLOYEE E2
WHERE E.Ssn <> E2.Ssn AND E.Dno = E2.Dno )

CPSC 343: Database Theory and Practice - Fall 2024
```

Subqueries in FROM

You can also use a SELECT query to create a relation to be used in the FROM clause.

- the result must be given an alias

CPSC 343: Database Theory and Practice • Fall 2024

Strategies for Writing Queries

Two strategies -

- start with FROM build a table that contains all of the rows in the desired result and all of the columns you need for the WHERE and SELECT clauses
- add WHERE to pick the desired rows
- add SELECT to pick the desired columns
- start with FROM build a table that contains all of the rows in the desired result and all of the columns that you need for the SELECT clause
- add WHERE to pick the desired rows, using a subquery if the condition involves information not in the FROM table
- add SELECT to pick the desired columns

CPSC 343: Database Theory and Practice • Fall 2024

27